

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : A62C 2/08, 3/00, E06B 5/00		A1	(11) International Publication Number: <b>WO 00/59579</b>
			(43) International Publication Date: 12 October 2000 (12.10.00)
(21) International Application Number: PCT/FI00/00298		(81) Designated States: AE, AG, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), DM, DZ, EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KR (Utility model), KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 7 April 2000 (07.04.00)			
(30) Priority Data: 990766 7 April 1999 (07.04.99) FI			
(71)(72) Applicant and Inventor: SUNDHOLM, Göran [FI/FI]; Ilmari Kiannonkuja 3, FIN-04310 Tuusula (FI).			
(74) Agent: KOLSTER OY AB; Iso Roobertinkatu 23, P.O. Box 148, FIN-00121 Helsinki (FI).			
		<b>Published</b> <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	

(54) Title: A BARRIER APPARATUS FOR RESISTING PASSAGE OF HARMFUL GASES THROUGH AN OPENING

(57) Abstract

The invention relates to a barrier apparatus for resisting passage of harmful gases from a space through a substantially vertical opening having a top, a bottom and lateral sides, the barrier apparatus comprising a suction arrangement for sucking gases and blowing arrangement for creating a flow of a medium. In order to effectively process harmful gases even in large spaces, the suction arrangement comprises at least one suction port (1) located near the top of the opening to provide blowing substantially along the width of the opening, the blowing arrangement comprises at least one blowing port (5) located near the bottom of the opening to provide blowing substantially along the width of the opening, a fluid coupling (8, 9) coupled between the suction arrangement and the blowing arrangement being provided and defining a fluid path between the suction port (1) and the blowing port (5), a spraying device (3) being arranged in the fluid path for driving gas from the suction port to the blowing port and being arranged for spraying a liquid in the fluid path for purifying and/or cooling media flowing through the fluid path. The invention also relates to a method of guiding and processing harmful gases near a doorway.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## **A BARRIER APPARATUS FOR RESISTING PASSAGE OF HARMFUL GASES THROUGH AN OPENING**

### **BACKGROUND OF THE INVENTION**

The invention relates to a barrier apparatus for resisting passage of  
5 harmful gases from a space through a substantially vertical opening having a top, a bottom and lateral sides, the barrier apparatus comprising a suction arrangement for sucking gases and blowing arrangement for creating a flow of a medium.

A barrier apparatus as described above is known for example from  
10 the International Patent Publication WO 93/10861. This reference discloses spray heads mounted above a doorway and arranged to produce a fog-like curtain of water. The spray heads operate at a high pressure, i.e. over 50 bar, and they produce in their immediate surroundings a high negative pressure that sucks smoke gases into the water spray. When the smoke gases are  
15 mixed with the spray, which preferably comprises a huge number of small droplets of water, the particles in the smoke gases are absorbed into the spray, thus mixing with the water droplets and being purified. With this method the harmful effects of poisonous gases have been greatly reduced. Another advantage is that when spray heads are arranged in small spaces, such as  
20 ship cabins and hotel rooms, smoke gases can be prevented rather effectively from spreading outside the small spaces, for example to corridors and further to other spaces.

The barrier apparatus disclosed in WO 93/10861 has been found to be especially effective in preventing smoke from spreading from small rooms  
25 to other spaces. Due to the operation described above, the barrier apparatus are also used to extinguish a fire. However, the spray means are not particularly applicable for use in large spaces, i.e. when smoke should be effectively absorbed and purified in big spaces.

The invention also relates to a method of guiding and processing  
30 harmful gases, especially smoke gases produced in a fire, near a substantially vertical opening, especially a doorway, and in a space comprising the harmful gases, in which method a flow of medium is created in the immediate vicinity of the opening.

WO 93/10861 discloses a method for guiding and purifying smoke  
35 gases near a doorway. Smoke gases can be guided and purified effectively when the spray means are located in a rather small space, which is subjected

to a fire and should thus be purified of smoke gases. However, if the space that should be purified is large and there is no fire, the purification of smoke gases is not as effective as it should be.

#### BRIEF DESCRIPTION OF THE INVENTION

5           An object of the invention is to provide a barrier apparatus and a method enabling effective processing or treating, even in a large space, of harmful gases, such as smoke gases produced in a fire, and other poisonous gases so as to reduce the harmful effects thereof.

10           For this purpose, the barrier apparatus according to the invention is characterized in that

          the suction arrangement comprises at least one suction port located near the top of the opening to provide suction substantially along the width of the opening,

15           the blowing arrangement comprises at least one blowing port located near the bottom of the opening to provide blowing substantially along the width of the opening,

20           a fluid coupling coupled between the suction arrangement and the blowing arrangement being provided and defining a fluid path between the suction port and the blowing port, a spraying device being arranged in the fluid path for driving gas from the suction port to the blowing port and being arranged for spraying a liquid in the fluid path for purifying and/or cooling media flowing through the fluid path.

25           Preferably the suction arrangement comprises a top suction duct located along the top of the opening and comprising said at least one suction port, and a first side suction duct and a second side suction duct located along opposite lateral sides of the at least one opening in the upper region thereof, and each side suction duct comprising at least one side suction port at a level below said at least one suction port. Such a construction makes the apparatus efficient and simple.

30           According to a preferred embodiment of the invention, the spraying device is arranged to spray liquid in the form of a fog-like spray. The fog-like spray purifies gases, e.g. smoke gases produced in a fire, very efficiently.

          Preferably the spraying device is a spray head located in a side suction duct.

35           Preferred embodiments of the barrier apparatus are described in the appended claims 2 to 9.

The sucking is carried out near the top of an opening, which is very advantageous when applying the present invention for purifying smoke gases produced in a fire. These smoke gases are hot and move therefore upwards and are likely present near the top of the opening.

5           The method according to the invention is characterized in that in an upper area of the opening in an area substantially corresponding to the width of the opening gases are sucked from the space into at least one suction port, and that near a bottom area of the opening in an area substantially corresponding to the width of the opening purified gases are blown from at least  
10 one blowing port into the space, said suction and said blowing being directed so as to at least substantially prevent air from penetrating via the opening into the space.

          Preferably the gases are guided above the opening and the medium is sprayed near the very bottom the opening.

15           Preferably in upper parts of the lateral sides of the opening gases are sucked from the space into further suction ports and from a level below said at least one suction port and above the middle of the lateral sides of the opening.

          When applying the method for guiding and purifying smoke gases  
20 produced in a fire, preferably a fog-like medium is sprayed with a spraying device at a high pressure to establish a flow path between said at least one suction port and said at least one blowing port and to provide the suction into said at least one suction port and to provide the blowing from said at least one blowing port, smoke gases being guided by said suction into the fog-like medium discharged from the spraying device in order to absorb in smoke gas  
25 particles. The fog-like medium is preferably an aqueous medium.

          A primary advantage of the invention is that harmful gases can be effectively transformed into a harmless form even if they are produced in a large space. When the invention is applied to extinguishing a fire, an important  
30 advantage is that the suction of air via the opening towards the fire is prevented rather efficiently, which greatly contributes to putting out the fire. Oxygen-poor purified gases are blown through the blowing port towards the space to be purified.

#### BRIEF DESCRIPTION OF THE FIGURES

35           The invention will be described below in greater detail by means of two examples with reference to the accompanying drawing, in which

Figure 1 is a front view of spray means arranged around a doorway,  
Figure 2 is a side view of the spray means of Figure 1,  
Figure 3 is an end view of a spray head,  
Figure 4 is a longitudinal view of the spray head according to Figure

5 3, and

Figures 5 and 6 show a second embodiment of the invention.

#### DETAILED DESCRIPTION OF THE FIGURES

In Figure 1, a doorway 20 is surrounded by a rectangular pipe system. The pipe system comprises a top suction duct in the form of a horizontal pipe section 10, a bottom blowing duct in the form of a horizontal pipe section 11, and side suction ducts in the form of vertical pipe sections 8 and 9 connecting the horizontal pipe sections. The aforementioned pipe sections 8 to 11 are provided with such lengths that the rectangle they form is slightly greater than the rectangle formed by the doorway, so that the pipe system in the doorway does not prevent the installation of a door therein, or passage through the doorway. The doorway may, particularly if it is high, also be higher than the pipe sections 8, 9: reference numeral 21 is drawn to such a doorway. The pipe sections 10 and 11 may in some applications be shorter than the width of the doorway. The pipe sections are in flow communication with one another. Pipe section 10 is provided along the length thereof with a number of suction ports in the form of openings 1 facing a room 30 or other space. Correspondingly, pipe section 11 is provided along the length thereof with a number of spray ports in the form of openings 5 facing the room 30. Pipe sections 8 and 9 are provided with side suction ports in the form of openings 2a and 2b, respectively, facing the room 30. The suction openings 2a, 2b are formed above the middle of the respective pipe sections 8 and 9 so as to extend substantially to the elbow of the pipe system. The suction openings 1, 2a, 2b and the spray openings 5 are formed on the walls of the respective pipe sections 10, 8, 9 and 11. These openings 1, 2a, 2b, 5 are directed for sucking and blowing respectively at an angle of between 20 and 90°, preferably between 40 and 90°.

Inside pipe sections 8 and 9 are provided spray heads 3 and 4, respectively, below the suction openings 2a and 2b. The spray heads 3, 4 are of a type that is able to operate at a high pressure, typically for example from 50 to 200 bar. In principle the high pressure can be any pressure that is higher

than a low pressure, i.e. about 12 bar. In practice a pressure range of from 20 to 300 bar covers the entire required area of pressure.

If the space 30 is to be protected against harmful gases arising from the space on the left side of the doorway in figure 2, a pipe system similar to the pipe system on the right side of the doorway should be installed on the left side of the doorway.

Figures 3 and 4 show a spray head that can be utilized in the present invention. The spray head is provided with a plurality of nozzles 100. When these spray heads operate at a high pressure, they spray a fog-like liquid-containing medium illustrated by reference numerals 6 and 7 along pipe sections 8, 9 and 11 to produce in their immediate vicinity a negative pressure. This negative pressure is apparent from a suction which prevails behind the spray heads, said suction, in turn, producing suction in the suction openings 1, 2a and 2b. The suction is illustrated in Figure 2 by reference numeral 31. A spray illustrated by reference numeral 32 in Figure 2 is directed from the spray openings 5 into the room 30.

The spray heads 3, 4 are connected via a supply line 33 to a hydraulic accumulator 13, which comprises a space 14 for an aqueous liquid and another space 15 for nitrogen gas or some other gas. The space 15 for gas is subjected to a high pressure, which makes the liquid move via the supply line 33 to the spray heads 3, 4, provided that a valve 34 is open. Unlike in the figure, the hydraulic accumulator 13 can comprise separate vessels for gas and liquid. A high pressure pump can be used as an alternative to the hydraulic accumulator.

The pipe sections 8 to 11 are preferably made of steel or plastic, and the diameter thereof varies from 30 to 300 mm, preferably from 50 to 200 mm, whereas the diameters of the openings 1, 2a, 2b, 5 provided in the pipe sections vary between 2 and 100 mm, preferably between 5 and 50 mm. Suitable dimensions, number of openings, the pressure to be used, and the volume of the hydraulic accumulator 13 are selected separately for each application. The flow resistance in the suction openings 1, 2a, 2b is preferably selected to correspond to the flow resistance in the spray openings 5.

The operation of the equipment shown in the figures will be described below.

Assume that smoke is produced in the space 30. A smoke detector (not shown in the figures) provided in the space 30 gives a signal, which

opens the valve 34 and also ensures directly or indirectly that other possible obstacles preventing the flow of liquid from the hydraulic accumulator 13 to the nozzles of the spray heads 3, 4 are removed. The hydraulic accumulator 13 starts to empty and an aqueous medium moves at a high pressure to the spray heads 3, 4 and further out of the spray heads in a fog-like or gaseous form (cf. arrows 6 and 7). A negative pressure produced in the suction openings 1, 2a, 2b sucks smoke and other gases into pipe section 10 and into the upper parts of pipe sections 8 and 9. In the lower parts of pipe sections 8 and 9 the smoke is mixed with the fog-like aqueous sprays 6, 7 and is thus purified. The sprays 6, 7 have a droplet size of typically under 400  $\mu\text{m}$ . Water containing smoke particles is discharged via a drain 12 provided at the lower end of the pipe section 11, so that the pipe section is constantly in working order for blowing oxygen poor purified gases via the spray openings 5.

When the spray means operate as described above, the space 30 is provided with constant circulation where smoke gases are sucked into the pipe system 8 - 11 and discharged therefrom back into the space in a purified form.

Figures 5 and 6 show another embodiment of the present invention. Corresponding reference numerals as in Figures 1 and 2 have been used for similar components. The pipe system in Figures 5 and 6 is installed in the middle of the doorway having the suction openings 1' and spraying openings 5' facing each other. Such a pipe system protects harmful gases from flowing to either side of the doorway, although not as effectively as two separate pipe systems positioned on respective sides of the doorway.

The invention is described above by means of two examples only, wherefore it is noted that the details of the invention can be implemented in various ways within the scope of the appended claims. Thus, the shape of the pipe system and the medium to be sprayed can differ from what is disclosed above, and the spray means can be used more generally to process and neutralize harmful gases and not necessarily to purify smoke gases produced in a fire. Two vertical pipe sections 8 and 9 and side openings 2a, 2b are not a necessity although very advantageous. Only one vertical pipe section, even without any side opening, can be contemplated for some applications. Naturally, the number of the suction openings 1, 2a, 2b and the spray openings 5 can differ from what is described above. Instead of a plurality of suction and spray openings, it is possible to use suction opening means and spray open-



ing means, respectively, that are in the shape of an elongated slot which extend substantially along the width of the doorway. The spray opening and suction opening means do not necessarily comprise a spray head since the spraying and suction can also be provided with other kinds of spraying means.

- 5 However, a spray head is particularly advantageous in providing the required spraying and suction. The number of the spray heads 3, 4 can differ from what is disclosed above: a single spray head arranged in pipe section 11 is sufficient. However, due to spray heads arranged in pipe sections 8 and 9 the structure of the pipe system can be made very simple and the operation
- 10 thereof effective. If the doorway 20 is large, i.e. pipe sections 8 and 9 are long, spray nozzles can be arranged in the pipe sections one after another, such that the rear or upper nozzle sprays towards the front or lower nozzle, which sucks in the medium sprayed from the rear or upper nozzle. With this arrangement the flow resistances in the pipe sections, no matter how great, do
- 15 not form an obstacle for spraying. The geometrical form of the doorway, or other opening through which harmful gases may not pass through, does not have to be a rectangle: it can e.g. be circular. The purification of gases can be done by a filter in addition to or as an alternative to the purification by means of a spraying device such as a spray head.

## CLAIMS

1. A barrier apparatus for resisting passage of harmful gases from a space through a substantially vertical opening having a top, a bottom and lateral sides, the barrier apparatus comprising a suction arrangement for sucking  
5 gases and blowing arrangement for creating a flow of a medium, **c h a r a c - t e r i z e d** in that

the suction arrangement comprises at least one suction port (1, 1') located near the top of the opening to provide suction substantially along the width of the opening,

10 the blowing arrangement comprises at least one blowing port (5, 5') located near the bottom of the opening to provide blowing substantially along the width of the opening,

a fluid coupling (8, 9, 8', 9') coupled between the suction arrangement and the blowing arrangement being provided and defining a fluid path  
15 between the suction port (1, 1') and the blowing port (5, 5'), a spraying device (3, 3') being arranged in the fluid path for driving gas from the suction port to the blowing port and being arranged for spraying a liquid in the fluid path for purifying and/or cooling media flowing through the fluid path.

2. A barrier apparatus as claimed in claim 1, comprising a first side  
20 suction port (2a) and a second side suction port (2b), said ports being located at opposite lateral sides of the opening in an upper region thereof, at a level below said at least one suction port (1).

3. A barrier apparatus as claimed in claim 1, wherein the suction arrangement comprises a top suction duct (10) located along the top of the  
25 opening and comprising said at least one suction port (1), and a first side suction duct (8) and a second side suction duct (9) located along opposite lateral sides of the opening in an upper region thereof, and each side suction duct comprising at least one side suction port (2a, 2b) at a level below said at least one suction port, and a bottom blowing duct (11) located along the bottom of  
30 the opening and comprising said at least one blowing port (5).

4. A barrier apparatus as claimed in claim 1, wherein the suction arrangement comprises a top suction duct (10') located along the opening and comprising said at least one suction port (1') and a bottom blowing duct (11') located along the bottom of the opening and comprising said at least one  
35 blowing port (5'), said at least one suction port and said at least one blowing port facing each other.

5 5. A barrier apparatus as claimed in claim 3 or 4, wherein the top suction duct (10), the bottom blowing duct (11) and the side suction ducts (8, 9) have a diameter between 30 and 300 mm and the diameters of the suction ports (2a, 2b) and said at least one blowing port (5) are between 2 and 100 mm.

10 6. A barrier apparatus as claimed in claim 3 or 4, wherein at least the first side suction duct (8) is coupled between the top suction duct (10) and the bottom blowing duct (11) to define the fluid path between said at least one suction port (1) and said at least one blowing port (5), and the spraying device (3) being arranged in the first side suction duct for driving gas from said at least one suction port to said at least one blowing port and wherein no suction ports are provided in an area below a height level midway between the top suction duct and the bottom blowing duct.

15 7. A barrier apparatus as claimed in any one of the preceding claims, wherein the spraying device (3) is arranged to spray the liquid in the form of a fog-like spray (6, 7).

20 8. A barrier apparatus as claimed in claim 3, wherein the top suction duct (10), the side suction ducts (8, 9) and the bottom blowing duct (11) are mounted on a face of a wall through which the opening is formed.

9. A barrier apparatus as claimed in claim 8, wherein said at least one suction port (1) and said at least one blowing port (5) are facing the space.

25 10. A method of guiding and processing harmful gases, especially smoke gases produced in a fire, near a substantially vertical opening, especially a doorway, and in a space comprising the harmful gases, in which method a flow of medium is created in the immediate vicinity of the opening, **characterized** in that in an upper area of the opening in an area substantially corresponding to the width of the opening gases are sucked from the space into at least one suction port (1), and that near a bottom area of the opening in an area substantially corresponding to the width of the opening purified gases are blown from at least one blowing port (5) into the space, said suction and said blowing being directed so as to at least substantially prevent air from penetrating via the opening into the space.


35 11. A method according to claim 10, wherein in upper parts of the lateral sides of the opening gases are sucked from the space into further suc-

tion ports (2a, 2b) and from a level below said at least one suction port (1) and above the middle of the lateral sides of the opening.


12. A method according to claim 10 or 11 for guiding and purifying smoke gases produced in a fire, wherein a fog-like medium is sprayed with a spraying device (3, 4) at a high pressure to establish a flow path between said at least one suction port (1) and said at least one blowing port (5) and to provide the suction into said at least one suction port (1) and to provide the blowing from said at least one blowing port (5), smoke gases being guided by said suction into the fog-like medium discharged from the spraying device in order to absorb in smoke gas particles.

13. A method according to claim 12, wherein the fog-like medium is an aqueous medium.

2  
L<sup>o</sup>  
L<sup>o</sup>



11



2/3

Fig. 3




Fig. 4




Fig. 6





Fig. 5



## INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 00/00298

## A. CLASSIFICATION OF SUBJECT MATTER

IPC7: A62C 2/08, A62C 3/00, E06B 5/00

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: A62C, E06B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5353879 A (SHIGEO WATANABE ET AL), 11 October 1994 (11.10.94), column 1, line 64 - column 2, line 13, abstract	10,11
A	--	1-9,12-13
Y	US 4986364 A (THOMAS W. CLARK), 22 January 1991 (22.01.91), column 1, line 52 - line 56; column 1, line 62 - column 2, line 7, figure 3, abstract	10,11
A	--	1-9,12-13



Further documents are listed in the continuation of Box C.



See patent family annex.

## \* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&amp;" document member of the same patent family

Date of the actual completion of the international search

1 Sept 2000

Date of mailing of the international search report

01-09-2000

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Tomas Gustafsson/Els

Telephone No. +46 8 782 25 00



## INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 00/00298

## C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 9739801 A1 (SHIN, DONG-WON), 30 October 1997 (30.10.97), page 2, line 23; page 4, line 14 - line 21, figures 1,2, abstract  --	1-13
A	US 5702299 A (GÖRAN SUNDHOLM), 30 December 1997 (30.12.97), column 1, line 19 - line 30, figure 2, abstract  --	1-13
A	DE 19825420 A1 (EWALD, HARTMUT), 9 December 1999 (09.12.99)  --	1-13
A	FR 2089320 A (PEIGNEUX ALPHONSE), 7 January 1972 (07.01.72), page 1, line 22 - line 30, figure 1  -- -----	1-13

**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

08/05/00

International application No.

PCT/FI 00/00298

Patent document cited in search report			Publication date	Patent family member(s)		Publication date
US	5353879	A	11/10/94	JP	3186275 A	14/08/91
				JP	3186276 A	14/08/91
				JP	3186277 A	14/08/91
				JP	3188911 A	16/08/91
-----						
US	4986364	A	22/01/91	NONE		
-----						
WO	9739801	A1	30/10/97	AU	2712897 A	12/11/97
				EP	0959953 A	01/12/99
				KR	131052 Y	15/12/98
				KR	180881 B	18/02/99
-----						
US	5702299	A	30/12/97	AU	673737 B	21/11/96
				AU	6571294 A	12/12/94
				CA	2160891 A	24/11/94
				CN	1123006 A	22/05/96
				EP	0703807 A	03/04/96
				FI	932135 D	00/00/00
				FI	955425 A	10/11/95
				JP	8510042 T	22/10/96
				NO	954540 A	10/11/95
				RU	2120317 C	20/10/98
				SG	47402 A	17/04/98
				WO	9426356 A	24/11/94
-----						
DE	19825420	A1	09/12/99	AU	4506299 A	30/12/99
				WO	9964723 A	16/12/99
-----						
FR	2089320	A	07/01/72	BE	748747 A	16/09/70
-----						